

2026 Rulebook

Golden Sands Speedway 4-Cylinder Mod
Jefferson Speedway Internationals
Slinger Speedway Super Beez
Midwest Dash Series



Index:

1 - Safety Equipment

- 2 - Car Eligibility**
- 3 - Chassis/Interior**
- 4 - Roll Cage**
- 5 - Suspension**
- 6 - Tread Width**
- 7 - Spindles & Hubs**
- 8 - Steering**
- 9 - Ride Height**
- 10 - Fuel Tank**
- 11 - Fuel Pump**
- 12 - Weight**
- 13 - Brakes**
- 14 - Radiator/Fan**
- 15 - Rear end - RWD**
- 16 - Transmission- RWD/FWD**
- 17 - Clutch & Flywheel**
- 18 - Starter**
- 19 - Ignition System**
- 20 - Battery**
- 21 - Air Intake/Air Filter**
- 22 - Carburetors**
- 23 - Fuel Injection**
- 24 - Exhaust Systems**
- 25 - Engine**
- 26 - Tires**
- 27 - Wheels**
- 28 - Body & Appearance**
- 29 - Tow Hooks**
- 30 - Transponder/Radios/Electronics**
- 31 - Local Track Visiting**
- 32 - Tech Inspection**
- 33 - Tear Down Claim**
- 34 - Dynometer Test**

1. SAFETY EQUIPMENT

1A. SEATS- Approved aluminum driver's seat required. Seat must be fastened to the frame/roll cage and located to give adequate distance from driver's arm to door bars. Shoulder supports on the right and left sides of the seat are highly recommended. Head support on the right side is required. Head support on the left side is recommended. Leg supports are recommended.

Full containment seats recommended. (No Carbon Fiber) Seat may not protrude outside 4 point upright or top cage halo.

1B. SAFETY BELTS *Belts must be dated within 3 years of the event date or newer. If belts have an expiration date, those belts WILL NOT be legal after that date.* SFI- approved minimum 3-inch wide lap belt, 2-inch wide with Hans or 3" shoulder harness and submarine (crotch) strap required. Competitors using the Hans device may use a standard three-inch (3") or the Schroth racing or equivalent two inch (2") wide shoulder strap. Schroth Racing shoulder strap system has been specifically designed for the use with the HANS device. Belts must be anchored to roll cage or frame. Minimum Grade "5" 1/2-inch bolts and hardware required. Shoulder harness must not be anchored lower than 2- inches below the driver's shoulder height. 6-point belts (double crotch strap) are recommended.

1C. DRIVING COMPARTMENT Cockpit must be completely sealed off from the engine compartment and fuel cell. Roll bar padding required around driver; *Recommended: Fire retardant padding.* A securely mounted operational 2-½ pound minimum fire extinguisher with gauge visible for inspection purposes is mandatory. Extinguisher must be mounted in a quick release bracket. Fire suppression systems are recommended. Driver-side window net required, minimum 16 inch by 20-inch ribbon or mesh style and must be mounted to the roll cage so the latch is at the top front of the window. Lower window net

mounting must be of a secure approved manner. Clearly labeled push-pull toggle type kill switch accessible from either side of the car is required.

A gas pedal toe bar (kick-up) is highly recommended. No driver-adjustable devices allowed while the car is in competition.

No carbon fiber interior components will be allowed, likewise, no carbon fiber or titanium components allowed anywhere on the car.

1D. DRIVER'S ATTIRE Complete SFI- approved fire-retardant driving suit and gloves required. Eye protection and a **Snell SA-2020** helmet or newer required. Snell "M" or D.O.T helmets are not allowed. Head and Neck restraints (HANS Type), fireproof shoes, are recommended. Officials will monitor items related to safety, but ultimately it is the responsibility of the driver to monitor, maintain, and update his safety equipment.

2. CAR ELIGIBILITY

Four cylinder, front or rear wheel drive compact cars only with model year 10 years old and older, and a wheelbase of 92" to 107". Wheelbase must be within 1/2-inch of stock. No full-size cars allowed; No SUVs, crossovers, or vans permitted. No convertibles allowed. No all-wheel drive allowed. No all wheel steering allowed. No rear engine allowed. No mid-engine allowed. All doors must be welded, chained, or bolted shut. Hood and trunk must be secured with two or more hood pins. Hood inner supports may be removed. All glass (head, tail, and marker lights) except windshield must be removed. You may replace the windshield with Lexan. Lexan windshields require approved bracing; 2 braces minimum are required. Plastic, trim, and items that could break, burn, or fall off, must be removed in and outside the car. Skirts, hood scoops, front air dam and a 5" max height rear spoiler blade may be installed. You may relocate the battery. If in the driver's compartment, must be covered with a marine case or similar; battery must have steel to steel tie downs. Anything that can be unbolted (hinges, brackets, etc.) may be removed. Aftermarket nose pieces are allowed "Rub rails" allowed between front and rear wheel wells. Ends must be chamfered and capped (no sharp edges).

3. CHASSIS/INTERIOR

Complete bumper-to-bumper steel unit-body must be retained. Full width original firewall and floor-pan required. Rear firewall must be added to isolate from fuel cell. Stress points may be reinforced from the strut tower forward.

The inner front framework in front of the spring pockets/strut towers may be cut out and replaced with tubing and from rear axle back can be cut out and replaced with tubing. 20 Gauge Floor pan minimum.

4. ROLL CAGE

All cars must have a well-constructed, properly welded and gusseted 6-point full width roll cage made of $1\frac{3}{4}$ " .090 wall tubing or equivalent. Main roll hoop must be behind the driver and be reinforced with a full x- bar configuration. Roll cage must be properly anchored to rocker box or floor with sandwich plates under each up-right. Cage must be reinforced from left to right with bars under the dash, along floorboards, and behind the driver in main roll hoop. At least two bars must extend from main roll cage rearward to frame kick- up or beyond. A minimum of four equally spaced horizontal bars required in the driver's door, three in passenger side door. Door bars must be connected with a minimum of two equally spaced vertical studs. Two angular bars must connect bottom door bar to rocker box. All welds in cage and door structure must be gusseted. Left side door bar deflector plates of min.1/8" steel required. Driver's foot protection required.

5. SUSPENSION 5A.RWD

Steel springs that are stock appearing may be used; however, they must fit in stock mounts and location. One spring per wheel assembly. Wedge bolts are allowed. Spring buckets may not protrude through stock floor pan.

Suspension parts must remain stock provided for that make and model on both sides of vehicle, except upper A-frames or strut mounts may be altered from stock to adjust camber and caster but not to exceed 6 degrees positive or

negative with driver out of car, non- adjustable rear control arms with stock dimensions and stock dimension bushings allowed.

Fabricated rear lower control arms of stock length, in stock locations with heim joints allowed but must be approved for safety and use. Hood may not be altered in any way due to alteration of upper strut mounts. No altering to lower A-frames and strut mounts. A-frames must be equal length right to left side.

No sectioning, channeling, altering, plating or chopping allowed. No ball joint spacers. bushings must be made of pliable material. No mono balls allowed. Stock appearing strut or shock price must not exceed \$275 MSRP, available at all normal retail outlets. Any non- adjustable type shock that fits in stock mounts in stock position allowed. No coil over shocks(no threaded shock/struts) shocks can be re-buildable but not adjustable. On non- strut cars, front upper shock mount may be raised. The extended mount may not exceed 3 inches in height and must remain "on center" and "in line" with original mounts. On leaf spring assemblies, lowering blocks are acceptable provided they do not alter or replace stock mountings. Single piece stock appearing sway bars only. May be adjustable; one bar per car. All suspension needs to be mounted in stock locations and tech staff must be able to tell what is stock locations. Any non-approved suspension modifications as per listed above rules, will require changes to an approved design and or weight penalties added to minimum spec weight, determined by tech officials.

5B FWD

FWD-Steel spring that fits in original mounts in original position allowed **MSRP under \$110**. One steel non-adjustable, non-rebuildable, shock/strut in stock location per wheel. Strut or shock price must not exceed \$200 MSRP, available at all normal retail outlets. Spring adjusters allowed, adjustable spring spacers where shock mounts through spring, screw type where shock mounts outside spring. Coil-over threaded collars allowed on strut type suspensions. **Non adjustable/non rebuildable threaded body strut allowed as long as it is under the \$200 MSRP.** (Competitor **MUST** be able to prove the threaded collar strut is

under the MSRP). Allowance of threaded collar struts for the 2027 season to be discussed. Adjustable leaf shackles allowed. Spring buckets may protrude through floor pan. Suspension parts including trailing links must remain of stock type for that make and model and year chassis. Upper A-frames and strut mounts may be altered for camber. Lower A-frames and strut rods must remain stock. One stock front and rear stabilizer bar allowed. Out of cockpit stabilizer adjusters allowed.

Stock trailing links required. Home built rear lower control arms of stock length, in the stock location with heim joints allowed. All suspension needs to be mounted in stock locations and tech staff must be able to tell what is stock locations. Any non-approved suspension modifications as per listed above rules, will require changes to an approved design and or weight penalties added to minimum spec weight, determined by tech officials.

6. TREAD WIDTH

Maximum track width is 75" as measured to the outside of the tires with toe-plates (1/8" tolerance allowed)

7. SPINDLES & HUBS

Stock, unaltered spindles and hubs required. Safety hubs allowed on right side.

8. STEERING

Stock, manual or power units only. No aftermarket components. Fabricated steering column must use 2 U-joints. Quick release removable steering wheel allowed and is highly recommended. Collapsible steering column recommended.

9. RIDE HEIGHT

Minimum ground clearance 3" (with driver) for all mechanical parts and hardware and body. (exhaust is an exception)

10. FUEL TANK

Fuel tanks or fuel cells must be mounted in the trunk area between the rear wheels as far forward as possible & mounted on top of floor pan and protected from rear collision, including protection bars and/or protection plates.

Tanks must be fastened with steel straps, bolts, and over-sized washers. A complete metal (minimum 20ga) firewall must be between the tank and the driver's compartment. If car came as a hatchback style, and fuel cell is in rear trunk area, a firewall will have to be built into car.

Fuel cells are highly recommended with a max capacity of **15 gallons** contained in a 22-gauge (minimum) fuel cell container. Fuel cell height can have no adjustment and a minimum of **8"** ground clearance is required at all times with driver in car. Fuel cell must be filled by opening rear deck lid.

Gasoline only; no additives allowed. No E-85 fuels or alcohol allowed. **Many factory fuel lines run through the driver compartment; therefore, these lines must be enclosed within a steel conduit pipe and clearly painted red with white lettering stating "FUEL LINE- DO NOT CUT."**

11. FUEL PUMP

Mechanical or electrical fuel pumps. Electrical pumps must be wired through oil pressure switch on the positive side or through the fuel injection control unit. Fuel pump must shut off when engine is not running with key on. Supply hose from cell to pump must be steel braided with AN type fittings.

12. WEIGHT

12A. FWD Minimum weight for all FWD cars will be 2350 lbs. With 58% max left side and 57% min front weight.

12B. RWD Minimum weight for all RWD cars will be 2300 lbs. With 58% max left side and 49% min front weight.

All weights include driver & are post-race minimums with No fuel allowance.

1. All weights: must be securely bolted to frame or cage, and be **painted** white, and have car number on it.

Car Type	Base Weight	Weight Percentage
All FWD Cars except below	2350	58% Left Max / 57% Front Min / max 62%
All RWD Cars except below	2300	58% Left Max / 51% Rear Max
Full Composite Body	+ 25LBS	58% Left Max
Variable Valve Timing	+50 Lbs	
Sportsman 790	+25 Lbs	1 right side tire
Sportsman 790	+75 Lbs	2 right side tires
Honda k Series 20	2450	
K Series 24	2600	
Ford 2.3 Carb	2300	
Ford 2.5 Carb	2350	
Ford 2.0 Duratec	2300	
Ford 2.3 Duratec	2400	

Ford 2.5 Duratec	2500	
B Series Engine	-5 0	
Dodge Engine	-5 0	

Additional weight may be added to any car at any time by the officials to ensure competitive balance within this class. If you plan to be fast or think you will be fast, be prepared this means bring weight and bolts. Weights may be added or deducted at the discretion of the tech staff to ensure a competitive balance is maintained.

13. BRAKES

13A. RWD- Four-wheel functioning brakes required at all times. Stock appearing drilled and slotted rotors are allowed. Rear brakes can be drum style or stock appearing disk brakes.

Single master cylinder in stock location only. Mounting of pedals may be adjusted subject to approval.

One hydraulic; proportioning valve rear brake adjuster allowed; must be out of the reach of the driver. No Wheel Fans or blowers allowed.

13B. BRAKES-FWD-Four-wheel functioning brakes required at all times Stock appearing drilled and slotted rotors are allowed. Stock rear disk brakes allowed. Single master cylinder. One hydraulic; proportioning valve rear brake adjuster allowed must be out of the reach of the driver. OEM anti-lock brakes (ABS) allowed No Wheel Fans or blowers allowed.

14. RADIATOR/FAN

Aluminum radiators are allowed. The only bracing allowed in front of the radiator is front loop. All cars will be required to have the overflow of the radiator discharge into a catch can of no less than 1-quart size. No anti-freeze permitted.

Fan shroud above fan mandatory, if running a mechanical fan.

15. REAR END-RWD

Locked, Limited slip, or Posi-Traction rear ends allowed. Rear end must be centered on rear springs as factory. No composite drive shafts. Drive shaft should be painted white and have a catch loop just behind the front u joint.

16. TRANSMISSION-RWD/FWD

OEM stock transmission; straight stick or automatic transmissions. Automatic transmissions must run torque converter, no gutting of torque converter. Car must be able to go forward and reverse from a complete stop. No removing gears from standard transmissions.

17. CLUTCH & FLYWHEEL

Clutch required. OEM manual transmission with all gears, including reverse, required. Two 1½" inspection holes, on opposite sides of bell housing, required for clutch inspection. Stock mounted operating starter required. HALF SHAFT-Heavy duty replacement parts allowed. Safety scatter shields or plated gas pedal area highly recommended.

18. STARTER

OEM production type starters only and must be in stock location.

19. IGNITION SYSTEM

OEM ignition components or OEM style replacements only. All electrical switches must be operable and must be located within reach of the driver.

A master ignition switch clearly labeled on-off, that is both accessible to driver and safety crew, must be centrally located inside the car. The on- off switch must

be wired to the battery cable in a manner that would cut power off to all electrical power to the vehicle. No on- board computer or other recording devices. No traction control devices. No lap timing devices or speed sensing devices are permitted. COMPUTER-All engine management controls, wiring and data port must be operating. Computer must be relocated (within wiring limits) for easy access. Reprogramming allowed. Master switch must kill ignition while the engine is running when turned off.

20. BATTERY

Only one standard automotive battery, not to exceed 12 volts, will be permitted, No light- weight batteries. Batteries must be securely mounted away from fuel container and lines. You may relocate the battery. If in driver's compartment, must be covered with a marine case or similar; battery must have steel to steel tie downs. Battery box cannot extend below frame.

21. AIR INTAKE/AIR FILTER

No cowl induction systems or funneling of air. All air shall be inlet through the air filter only. Absolutely no ducts or baffles permitted on or leading to the air cleaner or element. Fresh air openings of any type will not be permitted in the hood or cowl area.

22. CARBURETORS

1 Single carburetor only, any intake allowed. The Holley Ultra HP Carburetor is not allowed. The approved carburetors are the two-barrel 350 CFM (Holley 7448 only) or stock unaltered 500 CFM Stock Holley 4412 2 bbl. No alterations except removal of choke "Butterfly" allowed. Double return springs required.

Carburetor Rework Guidelines: No polishing, grinding, or drilling of holes allowed in body of carbs. Gasket surfaces may be machined for improved sealing. The choke may be removed, but all screw holes must be permanently sealed.

Choke horn may not be removed. Boosters may not be changed. Height, size, and shape must remain standard and unaltered. Venturi area must not be altered in any manner. Casting ring must not be removed.

Base plate must not be altered in shape or size. Stock butterflies must not be thinned or tapered. Idle holes may be drilled in butterflies. Screw ends may be cut even with shafts, but screw heads must remain standard. Throttle shafts must remain standard and must not be thinned or cut in any manner. Any attempt to pull outside air other than straight down through the venturi is not permitted. Accelerator pump discharge nozzle may not be changed. Jets may be changed; however, jets must be same type as supplied by carburetor manufacturer; dial-a-jet devices. No addition of any material, such as epoxy, may be added to carb or parts except to seal vacated external screw holes. Carburetor must be mounted

“straight ahead.” HP meter blocks must have no other holes except stock holes.

22A. CARB ADAPTER & GASKETS

Spacer must be centered on intake manifold. No bevels or any modifications will be permitted (tapered is acceptable). A one-piece two-hole paper gasket maximum 0.065-inch thickness that matches the exterior dimensions of the carburetor throttle plate must be installed between the carburetor and spacer. A one-piece paper gasket maximum 0.065-inch thickness must be installed spacer and intake manifold. Carburetor adapters/spacer limited to a 1.25” height with gasket total. No funneling devices or devices designed to get more air in to the engine will be permitted.

23. FUEL INJECTION

Throttle body max diameter 72mm. 1 fuel injector per cylinder. Electronic fuel injection (including intake manifold) for the car/engine used.

No forced induction, ram air induction, turbo or super-charging, nitrous systems, etc. allowed. Fuel rail with return line and fuel gauge allowed. Adapter/spacer limited to a 1.25” height with gasket total.

24. EXHAUST SYSTEMS

Exhaust must exit behind driver and meet 100 decibels Maximum at 100 feet. All exhaust highly recommended mufflers and to exit under car to meet this requirement; if right side exhaust exit is utilized; pipe may not stick out of body more than $\frac{1}{2}$ ". No dual exhaust. Cast iron exhaust manifold or aftermarket header allowed. Exhaust maximum of 2.5-inch I.D. from end of collector to exhaust pipe exit. No car expelling flame, smoke, or backfiring allowed. Any car not meeting the 100-decibel rating will add 25#'s for the night, & must remedy the issue before next visit.

25. ENGINE

Engine must be 4 cylinders, max displacement 2,500 cc. SOHC or DOHC engines (no turbos or superchargers) No Rotary Engines. Engine must be matching make (ford in a ford, ect). Type and composition of engine must remain as produced. Block, heads, intake and all other engine components must match. OEM block required with up to .040 overbore allowed. Crankshaft and stroke must remain as produced. Engines produced for non-domestic markets like JDM are allowed. Aftermarket oil pans & oil coolers are allowed. No dry sump oiling systems or Titanium parts allowed. Engines may not cross MFG lines; Ford engine in Chevy body, etc. Crankshaft Power pulley allowed, aftermarket pulley's & belt tensioners allowed.

25.1 ENGINE LOCATION

No motor setback or off set. Engines must be in the original position for Make and Model of the car. Solid motor mounts may be used.

ENGINE SPECS:

25A. RWD- Pistons must be flat top pistons or stock configuration only. Magnetic steel rods only.

25B. OIL PANS AND OIL COOLERS-Aftermarket oil pans & oil coolers are allowed. No dry sumps.

25C. CRANKSHAFT AND HARMONIC BALANCER-Crankshaft must be magnetic steel.

25D. CAMSHAFT No automatic cam timing devices allowed.

25E. VALVE LIFTERS-Steel hydraulic or solid lifters only. No mushroom or roller lifters permitted. Lifters must be the original size for the engine block being used. No rev kits permitted.

25F. ROCKER ARMS: FWD-Roller rocker arms allowed on push rod style motors. Stock roller tip cam followers allowed on engines that came with them from the factory. RWD-Stock style rocker arms or Roller rockers permitted.

25G. INTAKE-Intake manifolds must be stock OEM only, manufactured for the engine used.

25H. WATER PUMP- Mechanical water pumps in stock location only. No electric water pumps are allowed.

25I. Throttle Bodies: 72 mm maximum diameter.

26. TIRES

Hoosier 790 will be the specified tire. One Sportsman tire on the right side add 25 pounds and for 2 Sportsman tires on the right side add 75#. Tires will be monitored and assessed as needed. Teams may substitute DOT stamped tires with a tread wear rating of 300 or greater, a 60 series or taller sidewall, and with a maximum of a 215-section width or narrower. Tire Sizes may vary from left and right for stagger purposes. Tires may not extend out from the body of car by no more than 2". Chemical treatment of tires (softening) is not permitted and if found guilty will result in the disqualification from the event and loss of prize money and points. Drivers guilty of altering and/or chemical treatment of tires will also be suspended for the next night of racing. If a driver is found altering and/or chemical treatment of tires on the last night of competition, he/she will be disqualified for that night of points and prize money and deducted of all points

from the previous night of competition. Issues with tires must be discussed with Tech officials and their decision will be final.

27. WHEELS

Made for racing, 7-inch maximum width, steel wheels only. Only 13", 14" or 15" diameter wheels allowed. One-inch lug nuts required.

No bleeders allowed and only one valve stem per wheel maximum. Only 1 wheel spacer per wheel, maximum thickness of 1/4" allowed.

28. BODY AND APPEARANCE

28A. All exterior trim, lights, body molding, etc... must be removed. Air bags must be removed. All interior trim and flammable material must be removed from driver's compartment and trunk area. All glass must be removed, except front windshield, which may remain if deemed safe (no cracks or holes). All cars are required to have a front bumper cover, hood, both front fenders, all doors (2 or 4), both quarter panels, deck lid, and rear bumper cover. Roof must remain stock. A pillars, B pillars, and C pillars should remain stock, except where room is needed for roll cage, then they may be gutted for cage clearance. NO flat sided bodies allowed. Stock appearing front or rear bumpers and covers or made for racing bumpers and covers allowed. Downforce, shovel, or dirt late model bumper covers not allowed. Doors must be welded or bolted shut. Doors and interior may be skinned to allow room for roll cage and safety equipment. Skirting on front and sides allowed but must not be beyond 1/2" outside of tire and may not have sharp edges or ends. NO rear air diffusers allowed. NO splitters allowed. No venting of interior, roof, floor, fenders, doors, or trunk panels, (except fuel cell and drivers ventilation system) allowed. NO aftermarket hood scoops. Brake cooling ducts or vents connected to front bumper cover are permitted. Body panels must be securely fastened at the start of every event. Any body panel or wheel well opening deemed unsafe by Tech Official must be corrected before the car is allowed to compete. NO bars permitted through any body panel or bumper

flush to body. NO nerf style rub rails allowed, rub rails must be 1" by 1" steel

tubing or lexan decal protector type. Rub rails must not have sharp or ~~rough~~ edges.

28B. NO body panel, skirting, or bumper cover lower than 3" from the ground allowed. Cars must have STOCK frame, STOCK firewall, and STOCK floor pans, complete and unmodified. (In 2026 any car not meeting this rule will be required to weld in MINIMUM 20 gauge steel as floor pan.)

Trunk floor must be removed under fuel cell. Hood and trunk/hatch must be secured with a minimum of 2 hood pins.

28C. Front windshield may be replaced with Lexan (polycarbonate) or dirt screen. If using a Lexan windshield, you must have at least 1 center support. If using a dirt screen, you must have a minimum of 3 safety bars and must wear a full face helmet with eye protection. No material covering the passenger side window openings (lexan, or any other material). Tech Officials reserve the right to have teams make changes to allow track safety crews quick and easy access to the drivers compartment.

28D. Rear deck spoilers are allowed. NO roof mounted spoilers. MAXIMUM spoiler size is 5" tall and 60" wide. Maximum height of spoiler may not exceed past 5" above deck surface. Fabricated spoilers may be see through Lexan or may be metal if it does not limit the visibility of hand gestures and signals. The front edge of the spoiler must be within 4" of the rear of the deck lid, measured horizontally. Spoilers may not extent more than 3" beyond the rear edge of the deck lid measured horizontally. No window mounted spoilers or any other window mounted aerodynamic devices are allowed. Window mounted NACA ducts for driver's ventilation systems are permitted. NO verticals, shark fins, bill boards, or similar devices allowed.

28E. NO brake lights, strobe lights, undercar mounted lights, or headlamps allowed.

28F. Numbers: 18- inches on both sides, readable from the right side.

29. TOW HOOKS

Tow hooks on front and rear are required.

30. TRANSPONDERS/RADIOS/ELECTRONICS/MISC

30A. TRANSPONDER-150" behind front edge of car with clear view of track.

30B. Raceceivers are mandatory for Race Director Communications. Raceceiver frequency will vary from track to track.

30C. RADIOS-2-way-radios are not allowed.

30D. ELECTRONICS- No Data Logging gauges, or Data recording/acquisition equipment are allowed. No computer or video analysis equipment of any kind allowed. NO cell phones or Bluetooth devices permitted in the car during a race.

30E. CHAMPIONSHIP POINTS & MONEY-Championship points will be awarded per your finishing position. If driver is disqualified, drivers behind them do not advance.

30F. TEAM DRIVING-Not Allowed.

31. LOCAL TRACK VISITING EXCEPTION

Cars from local neighboring tracks that have similar but differing rules, and/or similar performance, may be allowed to participate during the 2026 season in the interest of welcoming competition. These cars will be granted temporary eligibility status for two weeks at the discretion of officials on a case-by-case basis for eligibility and rule book conformity.

32. TECH INSPECTION

All cars are subject to inspection ANYTIME before, during, or after a race; Officials reserve the right to disqualify cars, require changes, confiscate illegal parts etc. Any interference with any official(s) and his/her duties will result in an automatic disqualification, and/or possible suspension. Disqualification (except weight violation) is retroactive to ALL previous events competed in that race meet. Any driver/owner refusing to allow the track officials to inspect his car will lose points and money earned for the night. Driver must provide their own tools.

33. TEAR DOWN CLAIM

For a fee of \$750 any 4 Cylinder Mod driver may request to have the head, intake, exhaust manifold removed for inspection. If found legal, \$500 is awarded to the one inspected with \$250 retained by the officials. If illegal, the fee is

returned to the protester and the violator forfeits all money and points won that night. Officials can require air intake, fuel injectors, coil packs, computer, intake manifold and heads be removed and inspected for compliance. If components are found to be illegal they may be confiscated and destroyed. If found to be legal the owner will receive \$100 allowance for gaskets.

34. DYNOMETER TEST

At the request of the Tech Staff any engine/car can be required to be dynamometer tested to determine its compatibility with the intent of the rules.

ASM will be the official dyno facility of GSS.

ALL EQUIPMENT IS SUBJECT TO THE APPROVAL OF OFFICIALS. NO EQUIPMENT WILL BE CONSIDERED AS APPROVED BECAUSE IT HAS GONE THROUGH TECH UNNOTICED. ALL RACE CARS WILL BE SUBJECT TO INSPECTION BY TRACK OFFICIALS AT ANYTIME.